



The Non-Purge Sampling Option

www.idem.IN.gov

Mitchell E. Daniels, Jr.
Governor

Thomas W. Easterly
Commissioner

100 N. Ave., Indianapolis, IN 46204
Toll Free: (800) 451-6027

Original Guidance Created: May 27, 1998

Revised: November 3, 2009

Notice

The Technology Evaluation Work Group completed this evaluation of a “*The Non-Purge Sampling Option*” based on professional expertise and review of items listed in the “References” section of this document. The criteria for performing the evaluation are generally described in the IDEM OLQ technical memorandum, *Submittal Guidance for Evaluation of Innovative Remediation Technologies*.

This evaluation does not verify the effectiveness of the sampling technique in conditions not identified here. Mention of trade names or commercial products does not constitute endorsement or recommendation by the IDEM for use.

Background

Most of today’s well purging methods were developed during studies of water supply wells in the 1960’s and early 1970’s (Powell and Puls, 1997). The studied wells were usually steel cased with screens set below the top of the water table, and they were analyzed for inorganic water quality parameters.

The procedures used for sampling the water supply wells called for removing about three well volumes of water before sampling, because all the water in a well was thought to be “stagnant”, and not representative of water in the aquifer. This purging or removal of the “stagnant” water was deemed necessary before taking “fresh” samples. These procedures have since been carried over into the sampling of groundwater monitoring wells.

Problems Encountered

Traditional purging methods do present problems such as:

- Excessive agitation resulting in volatilization and degassing which gives erroneous results;

- If the well is purged dry (common in Indiana's low permeable areas) the recharge water cascading through the sand filter pack can lose up to 70% of volatile organic compounds (McAlary and Barker, 1987);
- Preferential recharge from more porous layers, biasing the sample;
- Increased turbidity from the disruption of the sand pack and surrounding soils;
- The large amount of time and effort, resulting in increased labor expense; and
- Disposal of large volumes of contaminated, purged water at considerable handling expense, and some risk of additional spills.

Studies to determine actual well flow patterns, including direct observation of colloidal suspensions and dyes in wells, have changed previously held dogma (Kearl, Korte and Cronk, 1992; Powell and Puls, 1993). Multiple studies have shown that while the water above and below a well screen may be stagnant, the water actually in the screened section flows across the well with no significant mixing of water in the screened interval with the stagnant water above or below. This holds true even for wells completed in low permeable materials (Robin and Gillham, 1987).

This shows that a sample taken from the screened area only (excluding stagnant layers above and below the screen) should be of "fresh" water, representative of the aquifer. Purging, with its attendant problems, could be avoided. Most normally constructed wells do not have much additional casing below the screen, and if present it could be avoided by restricting the depth of the sampling device. Stagnant water in the casing above the well screen is much more difficult to avoid. It should not be a factor in properly constructed wells measuring hydrocarbon contamination, because the screen is required to extend above the water table.

Papers have reported on the feasibility of not purging at all in sampling wells used for hydrocarbon monitoring. A large study sponsored by the Western States Petroleum Association (1996) used 13 different contractors to take 556 paired (non-purged and purged) samples from 101 sites. Overall, the non-purged samples averaged 9.5% higher benzene, ethylbenzene, toluene, and xylene (BTEX) results than purged samples. Most of the variation was found in samples taken using bailers or vacuum trucks to purge the wells, and from a few wells in coarse lithology. When these wells were removed from the data set, there was no difference in purged and non-purged samples at a 90% confidence level.

Another study by the California Regional Water Quality Control Board (Williams, et al, 1996) took 164 paired samples at 69 sites. Mean values for all BTEX components were slightly higher for non-purged samples than for purged ones. The cost for non-purging was 50% less than the purged sampling.

A similar study in New York by Shell (Byrnes, et al, 1996) utilized 168 paired samples from 13 sites, and found no significant difference at a 99% confidence level. No difference was found between samples from fine and coarse grained sediments.

Tests by Shell in Indiana analyzed 29 paired samples from 12 locations. No significant variations were found, except for two wells, both of which would be invalid for a non-purge sampling. One well had the screen below the water table, and the other contained free product.

Conclusion

These studies, and others like them, have demonstrated that purging may not be necessary under specific conditions when sampling hydrocarbon monitoring wells. Data are reliable, much time and money is saved, and waste handling and disposal problems of purged water are dramatically reduced.

The state of California now allows non-purging for hydrocarbon monitoring wells. The California EPA has issued a guidance document (California EPA, 1997) detailing procedures, conditions, and exceptions. Such an approach has a benefit to Indiana. Besides the money and time saved, much of this state is covered with low permeable soils, in which purging is difficult or impossible without running the wells dry, thus costing more time waiting for recharge and possibly biasing samples.

The Office of Land Quality, Science Services Branch, evaluated studies on well purging and sampling, and concluded that a non-purging (or passive) sampling methodology may provide comparable results in most cases to purged hydrocarbon samples, with a significant saving in time, money and waste generated (see Geological Services Technical Memorandum of May 27, 1998, Revised October 15, 2009). If the two methods vary at all, hydrocarbon analytical results from non-purged samples tend to be slightly higher than purged samples, which will result in a more conservative remediation. Accordingly, this non-purging method can be used as an option for monitoring hydrocarbons, if enough water for other sampling procedures can not be obtained from the well, and if the conditions outlined below are met. These requirements may be modified in the future, as additional information is acquired.

Please note that the term “passive sampling” is also used in reference to the application of diffusion bag samplers or grab samplers such as Hydrosleeve. This document does not apply to such uses or employment of these types of sampling systems.

Conditions for Utilizing the Non-Purge Option (Passive Sampling)

- 1) The method can be utilized only for wells used to monitor hydrocarbons: BTEX and methyl-tert-butyl ether (MTBE). It can not be used for metals, dense non-aqueous phase liquids (DNAPLs), or other pollutants.
- 2) It can be utilized only in unconfined aquifers.
- 3) The monitoring well must be properly constructed and developed (Indiana Water Well Drilling Rules 312 IAC 13).
- 4) The water table must be below the top of the well screen.

- 5) The monitoring well cannot contain free product or a visible sheen.
- 6) If dedicated bailers are used, they can not be stored within the well.
- 7) If a site closure is requested on a site that has been monitored by non-purge sampling, the final sampling event shall include both purged and non-purged samples from each well, to maintain consistency and satisfy closure rules for each program.
- 8) The sampling methodology and procedures must be detailed in the sampling section of each corrective action plan and progress report.
- 9) The procedures used must be approved by the IDEM program manager before non-purge sampling commences.
- 10) A separate table must be provided in each monitoring report, listing the screen depth and current water level of each monitoring well, to show that fluctuations have not raised the water table above the well screens. If water is above the screened interval, purged samples (such as low-flow) are required for that well.
- 11) Samples may be taken with bailers, in-well pumps, out-of-well pumps, or other forms of sampler approved by the IDEM Program Manager.
- 12) Bladder pumps or centrifugal pumps are preferred over bailers. Inertial lift and peristaltic pumps may not be used.
- 13) Any observed unusual conditions (i.e. turbid samples, well dry after 1st bailer, no observed recharge, unusual location of pump intake, etc.) should be noted in the sampling report to IDEM.

Further Information

If you have any additional information regarding this technology or any questions about the evaluation, please contact Steven H. Poe, Senior Geologist, at (317) 234-0992 or by e-mail at spoe@idem.IN.gov. This technical guidance document will be updated periodically, or if new information is acquired.

References

Byrnes, J. P., Brigalia, J. E., and Bealer, L. J. 1996. Evaluation of well purging in ground water sampling for BETX and MTBE. Proceedings of the Petroleum Hydrocarbons and Organic Chemicals in Ground Water Conference, National Ground Water Association, Westville, OH, pp. 221-235.

California EPA 1997. Utilization of non-purge approval for sampling of monitoring wells imported by petroleum hydrocarbon, BETX, and MTBE. Guidance document, Jan. 31, 3 p.

Geological Services Technical Memorandum: May 27, 1998, Revised October 15, 2009. Short review of the non-purging option for hydrocarbon monitoring wells.

Kearl, p.m., Korte, N. E. and Cronk, T. A. 1992. Suggested modification to ground water sampling procedures based on observations from colloidal borescope. Ground Water Monitoring Review 12, no. 2, pp 155-161.

McAlary, T. A. and Barker, J. F. 1987. Volatilization losses of organics during ground water sampling from low-permeability materials. Ground Water Monitoring Review 7, no. 4, pp. 63-68.

Powell, R. M. and Puls, R. W. 1997. Hitting the bulls-eye in groundwater sampling. Pollution Engineering, June, pp. 50-54.

Powell, R. M., and Puls, R. W. 1993. Passive sampling of groundwater monitoring wells without purging: Multilevel well chemistry and tracer disappearance. Journal of Contaminant Hydrology, vol. 12, pp. 51-77.

Robin, M. J. L. and Gilham, R. W. 1987. Field Evaluation of well purging procedures. Ground Water Monitoring Review. Vol. 7, no. 4, pp. 85-93.

Schoedel, L. 1997. Purge/no purge study conducted at Shell service stations. Personal communication to Steve Poe, April 21, 8 p.

Western States Petroleum Association, 1996 Final report: The California groundwater purging study for petroleum hydrocarbons. October 28, 92 p.

Williams, K., Martinez, A., Daugherty, S., and Lundegard, P.D., 1996. Groundwater sampling - a pilot study of the effects of well purging. Proceedings of the Petroleum Hydrocarbons and Organic Chemicals in Ground Water Conference, National Ground Water Association, Westville, OH, pp. 191-206.